

Transform Iterator

Author: David Abrahams, Jeremy Siek, Thomas Witt
Contact: dave@boost-consulting.com, jsiek@osl.iu.edu, witt@ive.uni-hannover.de
Organization: [Boost Consulting](#), [Indiana University Open Systems Lab](#), University of Hanover [Institute for Transport Railway Operation and Construction](#)
Date: 2004-11-01
Copyright: Copyright David Abrahams, Jeremy Siek, and Thomas Witt 2003.

abstract: The transform iterator adapts an iterator by modifying the `operator*` to apply a function object to the result of dereferencing the iterator and returning the result.

Table of Contents

[transform_iterator synopsis](#)
[transform_iterator requirements](#)
[transform_iterator models](#)
[transform_iterator operations](#)
[Example](#)

transform_iterator synopsis

```
template <class UnaryFunction,
          class Iterator,
          class Reference = use_default,
          class Value = use_default>
class transform_iterator
{
public:
    typedef /* see below */ value_type;
    typedef /* see below */ reference;
    typedef /* see below */ pointer;
    typedef iterator_traits<Iterator>::difference_type difference_type;
    typedef /* see below */ iterator_category;

    transform_iterator();
    transform_iterator(Iterator const& x, UnaryFunction f);

    template<class F2, class I2, class R2, class V2>
    transform_iterator(
        transform_iterator<F2, I2, R2, V2> const& t
```

```

        , typename enable_if_convertible<I2, Iterator>::type* = 0    // ex-
position only
        , typename enable_if_convertible<F2, UnaryFunction>::type* = 0 // ex-
position only
    );
    UnaryFunction functor() const;
    Iterator const& base() const;
    reference operator*() const;
    transform_iterator& operator++();
    transform_iterator& operator--();
private:
    Iterator m_iterator; // exposition only
    UnaryFunction m_f;   // exposition only
};

```

If `Reference` is `use_default` then the `reference` member of `transform_iterator` is `result_of<UnaryFunction(iterator)>::type`. Otherwise, `reference` is `Reference`.

If `Value` is `use_default` then the `value_type` member is `remove_cv<remove_reference<reference>>::type`. Otherwise, `value_type` is `Value`.

If `Iterator` models `Readable Lvalue Iterator` and if `Iterator` models `Random Access Traversal Iterator`, then `iterator_category` is convertible to `random_access_iterator_tag`. Otherwise, if `Iterator` models `Bidirectional Traversal Iterator`, then `iterator_category` is convertible to `bidirectional_iterator_tag`. Otherwise `iterator_category` is convertible to `forward_iterator_tag`. If `Iterator` does not model `Readable Lvalue Iterator` then `iterator_category` is convertible to `input_iterator_tag`.

transform_iterator requirements

The type `UnaryFunction` must be `Assignable`, `Copy Constructible`, and the expression `f(*i)` must be valid where `f` is an object of type `UnaryFunction`, `i` is an object of type `Iterator`, and where the type of `f(*i)` must be `result_of<UnaryFunction(iterator_traits<Iterator>::reference)>::type`.

The argument `Iterator` shall model `Readable Iterator`.

transform_iterator models

The resulting `transform_iterator` models the most refined of the following that is also modeled by `Iterator`.

- `Writable Lvalue Iterator` if `transform_iterator::reference` is a non-const reference.
- `Readable Lvalue Iterator` if `transform_iterator::reference` is a const reference.
- `Readable Iterator` otherwise.

The `transform_iterator` models the most refined standard traversal concept that is modeled by the `Iterator` argument.

If `transform_iterator` is a model of `Readable Lvalue Iterator` then it models the following original iterator concepts depending on what the `Iterator` argument models.

If <code>Iterator</code> models	then <code>transform_iterator</code> models
Single Pass Iterator	Input Iterator
Forward Traversal Iterator	Forward Iterator
Bidirectional Traversal Iterator	Bidirectional Iterator
Random Access Traversal Iterator	Random Access Iterator

If `transform_iterator` models Writable Lvalue Iterator then it is a mutable iterator (as defined in the old iterator requirements).

`transform_iterator<F1, X, R1, V1>` is interoperable with `transform_iterator<F2, Y, R2, V2>` if and only if `X` is interoperable with `Y`.

transform_iterator operations

In addition to the operations required by the concepts modeled by `transform_iterator`, `transform_iterator` provides the following operations.

```
transform_iterator();
```

Returns: An instance of `transform_iterator` with `m_f` and `m_iterator` default constructed.

```
transform_iterator(Iterator const& x, UnaryFunction f);
```

Returns: An instance of `transform_iterator` with `m_f` initialized to `f` and `m_iterator` initialized to `x`.

```
template<class F2, class I2, class R2, class V2>
transform_iterator(
    transform_iterator<F2, I2, R2, V2> const& t
    , typename enable_if_convertible<I2, Iterator>::type* = 0 // expo-
    sition only
    , typename enable_if_convertible<F2, UnaryFunction>::type* = 0 // expo-
    sition only
);
```

Returns: An instance of `transform_iterator` with `m_f` initialized to `t.functor()` and `m_iterator` initialized to `t.base()`.

Requires: `OtherIterator` is implicitly convertible to `Iterator`.

```
UnaryFunction functor() const;
```

Returns: `m_f`

```
Iterator const& base() const;
```

Returns: `m_iterator`

```
reference operator*() const;
```

Returns: `m_f(*m_iterator)`

```
transform_iterator& operator++();
```

Effects: `++m_iterator`

Returns: `*this`

```
transform_iterator& operator--();
```

Effects: `--m_iterator`

Returns: `*this`

```
template <class UnaryFunction, class Iterator>
transform_iterator<UnaryFunction, Iterator>
make_transform_iterator(Iterator it, UnaryFunction fun);
```

Returns: An instance of `transform_iterator<UnaryFunction, Iterator>` with `m_f` initialized to `f` and `m_iterator` initialized to `x`.

```
template <class UnaryFunction, class Iterator>
transform_iterator<UnaryFunction, Iterator>
make_transform_iterator(Iterator it);
```

Returns: An instance of `transform_iterator<UnaryFunction, Iterator>` with `m_f` default constructed and `m_iterator` initialized to `x`.

Example

This is a simple example of using the `transform_iterators` class to generate iterators that multiply (or add to) the value returned by dereferencing the iterator. It would be cooler to use lambda library in this example.

```
int x[] = { 1, 2, 3, 4, 5, 6, 7, 8 };
const int N = sizeof(x)/sizeof(int);

typedef boost::binder1st< std::multiplies<int> > Function;
typedef boost::transform_iterator<Function, int*> doubling_iterator;

doubling_iterator i(x, boost::bind1st(std::multiplies<int>(), 2)),
    i_end(x + N, boost::bind1st(std::multiplies<int>(), 2));

std::cout << "multiplying the array by 2:" << std::endl;
while (i != i_end)
    std::cout << *i++ << " ";
std::cout << std::endl;

std::cout << "adding 4 to each element in the array:" << std::endl;
std::copy(boost::make_transform_iterator(x, boost::bind1st(std::plus<int>(), 4)),
    boost::make_transform_iterator(x + N, boost::bind1st(std::plus<int>(), 4)),
    std::ostream_iterator<int>(std::cout, " "));
std::cout << std::endl;
```

The output is:

```
multiplying the array by 2:
2 4 6 8 10 12 14 16
adding 4 to each element in the array:
5 6 7 8 9 10 11 12
```

The source code for this example can be found [here](#).